




Thyristor rapide





Descriptif : thyristor rapide de puissance.

Application : haute fréquence, possibilité de tri pour mise en série ou parallèle.

BOÎTIER VISSÉ

Type	V_{RRM}/V_{DRM} V	$I_T (AV)$ A (°C)	Rapidité μs	Boitier mm	Code
GTF 08-0.1-XX M6	800	16 (80)	12 à 32	M6	M6
GTF 08-0.2-XX M6	800	20 (80)	12 à 32	M6	M6
GTF 08-0.2-XX M6	800	25 (80)	12 à 32	M6	M6
GTF 08-01-32 1/2	800	100 (70)	32	1/2	1/2
GTF 06-0.6-12 1/2	600	60 (70)	12	1/2	1/2
GTF 10-0.6-16 1/2	1000	60 (70)	16	1/2	1/2
GTF 12-0.6-20 1/2	1200	60 (70)	20	1/2	1/2
GTF 16-0.6-32 1/2	1600	60 (70)	32	1/2	1/2
GTF 08-0.8-20 1/2	800	80 (75)	20	1/2	1/2
GTF 12-0.8-25 1/2	1200	80 (75)	25	1/2	1/2
GTF 06-01-32 1/2	600	100 (75)	32	1/2	1/2
GTF 08-0.1-XX 1/4	800	15 (75)	10 à 20	1/4	1/4
GTF 06-0.2-XX 1/4	600	20 (75)	10 à 20	1/4	1/4
GTF 06-0.2-XX 1/4	600	25 (75)	10 à 20	1/4	1/4
GTF 06-01-20 M12	600	100 (70)	32	M12	M12
GTF 08-0.6-12 M12	800	63 (75)	12	M12	M12
GTF 10-0.6-16 M12	1000	63 (75)	16	M12	M12
GTF 12-0.6-20 M12	1200	63 (75)	20	M12	M12
GTF 16-0.6-32 M12	1600	63 (75)	32	M12	M12
GTF 08-0.8-20 M12	800	80 (75)	20	M12	M12

M6	1/4	1/2
		

M12	3/4		M20
	H32	H45	
			

Thyristor rapide

Descriptif : thyristor rapide de puissance.

Application : haute fréquence, possibilité de tri pour mise en série ou parallèle.




BOÎTIER VISSÉ

Type	V_{RRM}/V_{DRM} V	$I_T (AV)$ A (°C)	Rapidité μs	Boitier mm	Code
GTF 12-0.8-25 M12	1200	80 (75)	25	M12	M12
GTF 06-01-32 M12	600	100 (75)	32	M12	M12
GTF 16-01-40 3/4	1600	125 (80)	40	3/4	3/4H32
GTF 22-01-60 3/4	2200	125 (80)	60	3/4	3/4H32
GTF 10-01-XX 3/4	1000	175 (70)	12 à 16	3/4	3/4H32
GTF 12-02-20 3/4	1200	225 (80)	20	3/4	3/4H45
GTF 16-02-40 3/4	1600	225 (80)	40	3/4	3/4H45
GTF 08-03-20 3/4	800	300 (80)	20	3/4	3/4H45
GTF 12-03-25 3/4	1200	300 (80)	25	3/4	3/4H45
GTF 16-01-40 M20	1600	125 (80)	40	M20	M20
GTF 22-01-60 M20	2200	125 (80)	60	M20	M20
GTF 10-01-XX M20	1000	175 (70)	12 à 16	M20	M20
GTF 12-02-20 M20	1200	225 (80)	20	M20	M20
GTF 16-02-40 M20	1600	225 (80)	40	M20	M20
GTF 08-03-20 M20	800	300 (80)	20	M20	M20
GTF 12-03-25 M20	1200	300 (80)	25	M20	M20

Terminaison :

Nos semiconducteurs vissés sont proposés en standard en tresse souple.

Pour toute terminaison spéciale nous consulter.

M6	1/4	1/2	
			
M12	3/4		M20
	H32	H45	
